



The mark of
responsible forestry



Supermesh & Superfilm

Speciality Plywood

Durable Phenolic Plywood Panels

Crafted from strong, stable, exterior-glued plywood, these panels are built to withstand demanding environments.

Each board is coated with a tough, hard-wearing phenolic overlay for long-lasting durability and reliable performance. Available in both smooth and anti-slip finishes, they offer flexibility for a wide range of applications.

For added protection, every panel is sealed with an acrylic edge finish to guard against moisture and wear.

Heavy-Duty Applications

Specifically designed for vehicle flooring, loading platforms, and scaffolding, this plywood delivers exceptional strength and stability.

Manufactured from engineered hardwood veneers and bonded with 100% exterior-grade phenol formaldehyde resin, it provides superior durability, resistance to wear, and long-lasting performance in demanding conditions.

Supermesh & Superfilm

Speciality Plywood



The mark of
responsible forestry

Specifications

Dimensions	2500 x 1250mm, 2500 x 1220mm, 2440 x 1220mm (other cut sizes available on request)
Thickness	9mm (7ply), 12mm (9ply), 15mm (11ply), 18mm (13ply), 21mm (15ply), 24mm (17ply), 27mm (19ply)
Average density	Approximately 700 kg/m ³
Film pattern	Mesh (rice pattern) and Smooth
Film colour	Black or Dark Brown
Performance	Declaration of Performance (DOP), available on request

Standards & Compliance

Sustainably Sourced: Manufactured from environmentally sustainable materials.

Certified Options: Available with FSC® or PEFC certification.

Readily Available: Prompt supply through select distributors.

High Standards: Produced to exacting standards and compliant with EN 314-2, Class 3 exterior bond (BS EN 13986).

Low Emissions: Meets formaldehyde emissions Class E1.

Contact us by email on info@ptgroup.ltd.uk
or call **+44-1223-833042**



PT Timber Ltd. 7a St Peters Street, Duxford
Cambridge CB22 4RP, United Kingdom
www.pttimber.com

